

Pony



9000 Btu



12000 Btu
18000 Btu
24000 Btu

Wide Angle Air Outlet System

Four dimension air outlet, enjoy the comfortable feeling everywhere.

Integrtd Design

Rear case and water pan are combined for easy installation and maintains.



Non Inverter



Comfortable Sleep Mode



LED Display



Timer



Compact Design



Auto Clean



Automatic Operation



'Turbo' Button



Clock Display



Self-diagnosis



Auto Restart



Lock

Model			GWC09MA-E1NNA3K	GWC12MA-K1NNA3H	GWC18NC-K1NNA3A	GWC24ND-K1NNA3A
Function			Cooling	Cooling	Cooling	Cooling
Capacity	Cooling	Btu/h(H/S/L)	9000	12000	18000	24000
EER		W/W	3.16	2.81	2.41	2.50
		Btu/h/W	10.78	9.59	8.22	8.53
Star Rating			3	2	2	2
Power Supply			1Ph,220-240 V,50Hz			
Power Input	Cooling	W(H/S/L)	806	1177	1798	2287
Rated Current	Cooling	A(H/L)	6.94	8.00	12.01	14.60
Indoor Unit						
Airflow Volume	Indoor	m ³ /h	454.4	479.2	572.8	850
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	40/37/35/32	41/38/35/32	43/39/36/33	48/45/41/37
Outline Dimension	WxHxD	mm	730x255x170	790x265x170	845x275x186	940x200x298
Package Dimension	WxHxD	mm	793x248x340	873x370x251	918x258x370	1013x300x383
Net Weight/Gross Weight	Indoor	kg	8/10.5	9/10.5	10/13	13/17
Outdoor Unit						
Sound Pressure Level	Outdoor	dB(A)	50	52	57	56
Piping Connection	Gas	mm	φ9.52	φ12	φ12	φ12
	Liquid	mm	φ6	φ6	φ6	φ6
Outline Dimension	WxHxD	mm	720x428x310	848x540x320	848x540x320	913x680x378
Package Dimension	WxHxD	mm	768x353x490	881x595x363	881x595x363	997x740x431
Net Weight/Gross Weight	Outdoor	kg	25/27.5	31/33.5	41/46	46/52
RefrigerantR22			R22			